



TEMPO COAX SPECIFICATIONS

SPECIFICATIONS	TEMPO COAX 4 "	TEMPO COAX 5 "	TEMPO COAX 6 "	TEMPO COAX 5x7 "	TEMPO COAX 6x9 "	
Nominal Impedance	4 Ohm	4 Ohm	4 Ohm	4 Ohm	4 Ohm	
Power Handling	50W	100W	110W	90W	140W	
Max. Transient Power Handling	120W	200W	200W	200W	250W	
Sensitivity (2.83V/1M)	85dB	89dB	90dB	90dB	91dB	
Frequency Response	70-22000Hz	55-22000Hz	40-22000Hz	50-22000Hz	35-22000Hz	
Crossover Point	4000Hz	4000Hz	4000Hz	4000Hz	3800Hz	
Voice Coil Diameter	Woofer:	25mm (1.00")	25mm (1.00")	25mm (1.00")	25mm (1.00")	30mm (1.18")
	Tweeter:	25mm (1.00")	25mm (1.00")	25mm (1.00")	25mm (1.00")	25mm (1.00")
Voice Coil Wire	Woofer:	Copper	Copper	Copper	Copper	Copper
	Tweeter:	Copper	Copper	Copper	Copper	Copper
Magnet System	Woofer:	High grade ferrite	High grade ferrite	High grade ferrite	High grade ferrite	High grade ferrite
	Tweeter:	Neodymium	Neodymium	Neodymium	Neodymium	Neodymium
Mounting Depth	48mm (1.89")	60mm (2.36")	64mm (2.51")	60mm (2.36")	86mm (3.38")	

* Morel operates a policy of continuous products design improvement, consequently specifications are subject to alteration without prior notice.